STRAIT-FLEX®

New Concept Drywall Products

OS- 400

DESCRIPTION (Speed, Perfection and Longevity)	Patented PVC tight fibered cotton composite corner tape with diamond-punched paper edging that is 4 ” wide, **.**025**”** thick and comes in 8, 9, and 10 foot lengths. OS-400 has PUR-laminated nose to protect against paper fuzz-ups during finishing and sanding.
ADVANTAGES	• **No callbacks on outside 90-degree corners due to cracking or denting.** • **OS-400 creates a fast, perfect, outside corner that can be installed by an apprentice.** • **Damage proof design.** • **Withstands settling, lumber shrinkage and temperature variation.** • **Diamond-punched paper ensures ultimate bonding and faster drying.** • **Faster hanging and finishing time (guarantee).** • **Installation does not require fasteners, stapling, or any special tools.** • **Can run through hopper to mud both sides.** • **Material can be second coated immediately.** • **Material will not fuzz-up during sanding.** • **Water resistant, rustproof.** • **Saves 25-50% on installation time.** • **Second coat of compound can be applied immediately-very light skim coat to finish.** • **Use in place of metal corner bead.**
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
DIRECTIONS	• Apply using liberal coat of all-purpose compound to corner or angle with joint knife. OS-400 can also be put through a hopper to mud either side. • Press OS-400 into wet compound, adjust if necessary to create straight line and remove excess compound. • Apply second coat of compound “immediately”, lightly skim coat surface of OS-400. • Apply final coat if required, same as second coat and let dry. Sand lightly to smooth surface. • OS-400 will not fuzz up during sanding. Painted surface of OS-400 must be thoroughly dry before applying second paint coat.
STORAGE	Store in dry place protected from moisture

Submittal Approvals:

Job Name:	
Contractor:	Date: